CS 565, Jens Palsberg Oct 17, 1999

Lecture Note 4: Continuation Passing Style

Contents

1 Overview 2

2 From Scheme to Tail Form 3

3 From Tail Form to First-Order Form 18

3.1 Continuations as a Datatype 19
3.2 Representation-Independent Code 19
3.3 Procedural Representation of Continuations 20
3.4 Abstract Syntax Tree Representation . . . 21
3.5 Nifty Tree Representation 22
3.6 Even Niftier Tree Representation 23
3.7 List Representation of Continuations . . . 28
3.8 Stack Representation of Continuations . . 33
3.9 Clever Representation of Continuations . . 41

4 From First-Order Form to Imperative Form 46

1 Overview

This note shows how to translate a Scheme program into efficient low-level code. The translation is in a number of steps.

1. From a Scheme program to a Scheme program in *tail form*. The idea is to transform the program such that functions never return. This is done by introducing *continuations*.

2. From a Scheme program in tail-form to a Scheme program in *first-order form*. The idea is to transform the program such that all functions are defined at the top level. This is done by representing the continuations as first-order data structures.

3. From a Scheme program in first-order form to a Scheme program in *imperative form*. The idea is to transform the program such that functions take no arguments. This is done by passing the arguments in a fixed number of global variables. It is possible to avoid using a stack because the program is in tail form.

4. From a Scheme program in imperative form to C, machine code, etc. A Scheme program in imperative form is so close to machine code that the translation is mostly a matter of replacing each function call with a jump.

This note covers the first three steps. The reader will have no difficulty working out the details of the fourth step.

2 From Scheme to Tail Form

Recursive vs. *iterative* behavior:

```
(define fact
  (lambda (n)
    (if (zero? n) 1 (* n (fact (sub1 n))))))

(define fact-iter
  (lambda (n)
    (fact-iter1 n 1)))

(define fact-iter1
  (lambda (n a)
    (if (zero? n) a (fact-iter1 (sub1 n) (* n a)))))

In Java:

\begin{verbatim}
  int fact(int n) {
    int a=1;
    while (n!=0) {
      a=n*a;
      n=n-1;
    }
    return a;
  }
```

```
  (fact 4)
= (* 4 (fact 3))
= (* 4 (* 3 (fact 2)))
= (* 4 (* 3 (* 2 (fact 1))))
= (* 4 (* 3 (* 2 (* 1 (fact 0)))))
= (* 4 (* 3 (* 2 (* 1 1))))
= 24
```

```
  (fact-iter 4)
= (fact-iter1 4 1)
= (fact-iter1 3 4)
= (fact-iter1 2 12)
= (fact-iter1 1 24)
= (fact-iter1 0 24)
= 24
```

A program with iterative behavior can be written in flowchart-like pseudocode:

```
fact:       a := 1
fact-iter1: if (zero? n) then return a
                         else begin a := n*a
                                    n := n-1
                                    goto fact-iter1
                              end
```

```
(define even-length?
  (lambda (l)
    (if (null? l) #t (odd-length? (cdr l)))))

(define odd-length?
  (lambda (l)
    (if (null? l) #f (even-length? (cdr l)))))
```

```
even-length?: if (null? l) then return #t
                           else begin l := (cdr l);
                                      goto odd-length?
                           end
odd-length?:  if (null? l) then return #f
                           else begin l := (cdr l);
                                      goto even-length?
                           end
```

Below is a grammar which describes programs that look like the ones above. We need two non-terminals: *SimpleExp*, for expressions that can go on the right-hand sides of assignments, etc., and *TailFormExp*, for the programs themselves.

TailFormExp	::=	*SimpleExp*
	|	(*SimpleExp* $SimpleExp_1 \ldots SimpleExp_n$)
	|	(`if` *SimpleExp TailFormExp TailFormExp*)
	|	(`begin` $SimpleExp_1 \ldots SimpleExp_n$ *TailFormExp*)
SimpleExp	::=	*Identifier*
	|	*Constant*
	|	(*PrimitiveOperation* $SimpleExp_1 \ldots SimpleExp_n$)
	|	(`set!` *Identifier SimpleExp*)
	|	(`lambda` ($Identifier_1 \ldots Identifier_n$) *TailFormExp*)

Tail form positions are those where the subexpression, when evaluated, gives the value of the whole expression (no promises or wrapping). All other positions must be simple.

A more complete grammar:

TailFormExp	::=	(`cond` (*SimpleExp TailFormExp*) ...)
	|	(`let` (*SimpleDeclList*) *TailFormExp*)
	|	(`letrec` (*SimpleDeclList*) *TailFormExp*)
SimpleDeclList	::=	$SimpleDecl_1 \ldots SimpleDecl_n$
SimpleDecl	::=	(*Identifier SimpleExp*)

Note: our *SimpleExp* corresponds to what the book calls "simple *and* tail-form".

Examples

```
(car x)                          tail form (also simple)

(car (cdr x))                    tail form (also simple)

(car (f x))                      not tail form

(f (car x))                      tail form

(lambda (v) (k (+ v 1)))         tail form

(lambda (v) (+ (k v) 1))         not tail form

(if (zero? x) (f (+ x 1)) (g (- x 1)))   tail form

(if (zero? x) (+ (f x) 1) (g (- x 1)))   not tail form

(if (p x) (f (+ x 1)) (g (- x 1)))       not tail form

(if (p (car x)) (f (+ x 1)) (g (- x 1))) not tail form

(lambda (x)                       ; not tail form
  (if (zero? x) 0 (+ (f (sub1 x)) 1)))

(lambda (x)  ; tail form
  (if (zero? x) 0 (f (sub1 x) (lambda (v) (k (+ v 1))))))

(lambda (n a)  ; tail form
  (if (zero? n) a (fact-iter1 (sub1 n) (* n a))))
```

Converting to Tail Form

```
(define fact
  (lambda (n)
    (if (zero? n) 1 (* n (fact (sub1 n))))))
```

Typical state:

```
(* 6 (* 5 (* 4 (fact 3))))
```

Let's write another version of `fact`, called `(fact-cps n g)`, which computes `(g (fact n))`.

```
(define fact-cps
  (lambda (n g)
    (if (zero? n)
        (g 1)
        (fact-cps (sub1 n)
  (lambda (v) (g (* n v)))))))
```

The Transformation Rules

```
(define foo
  (lambda (x y) -----))

==>

(define foo-cps
  (lambda (x y k) (k --------)))
```

```
(k (foo a (sub1 n)))

==>

(foo-cps a (sub1 n) k)
```

```
(k (----- (foo a (sub1 n)) -----))

==>

(foo-cps a (sub1 n) (lambda (v) (k (----- v ----))))
```

```
(define remove-all
  (lambda (a lsym)
    (cond
      ((null? lsym) '())
      ((eq? a (car lsym))
       (remove-all a (cdr lsym)))
      (else
(cons
  (car lsym)
  (remove-all a (cdr lsym)))))))

==>

(define remove-all-cps
  (lambda (a lsym k)
    (k (cond
         ((null? lsym) '())
         ((eq? a (car lsym))
          (remove-all a (cdr lsym)))
         (else
           (cons
             (car lsym)
             (remove-all a (cdr lsym))))))))
```

```
(define remove-all-cps
  (lambda (a lsym k)
    (cond
      ((null? lsym) (k '()))
      ((eq? a (car lsym))
       (k (remove-all a (cdr lsym))))
      (else
        (k
          (cons
            (car lsym)
            (remove-all a (cdr lsym))))))))

;; (k (cons
;;      (car lsym)
;;      (remove-all a (cdr lsym))))
;;
;; ==>
;;
;; (remove-all-cps a (cdr lsym)
;;   (lambda (v)
;;     (k (cons (car lsym) v))))

(define remove-all-cps
  (lambda (a lsym k)
    (cond ((null? lsym) (k '()))
          ((eq? a (car lsym))
           (remove-all-cps a (cdr lsym) k))
          (else
            (remove-all-cps a (cdr lsym)
              (lambda (v) (k (cons (car lsym) v))))))))
```

```
(define subst
  (lambda (old new s)
    (if (pair? s)
        (cons (subst old new (car s))
              (subst old new (cdr s)))
        (if (eq? s old) new s))))

==>

(define subst-cps
  (lambda (old new s k)
    (if (pair? s)
      (k (cons (subst old new (car s))
               (subst old new (cdr s))))
      (if (eq? s old)
          (k new)
          (k s)))))

==>

(define subst-cps
  (lambda (old new s k)
    (if (pair? s)
      (subst-cps old new (cdr s)
        (lambda (cdr-val)
          (k (cons (subst old new (car s)) cdr-val))))
      (if (eq? s old)
        (k new)
        (k s)))))
```

```
(define subst-cps
  (lambda (old new s k)
    (if (pair? s)
        (subst-cps old new (cdr s)
          (lambda (cdr-val)
            (subst-cps old new (car s)
              (lambda (car-val)
                (k (cons car-val cdr-val))))))
        (if (eq? s old)
          (k new)
          (k s)))))
```

Alternatively, we can compute the car first:

```
(define subst-cps
  (lambda (old new s k)
    (if (pair? s)
        (subst-cps old new (car s)
          (lambda (car-val)
            (subst-cps old new (cdr s)
              (lambda (cdr-val)
                (k (cons car-val cdr-val))))))
        (if (eq? s old)
          (k new)
          (k s)))))
```

```
(define subst-with-letrec
  (lambda (old new s)
    (letrec
      ((loop
         ;; (loop s) = (subst old new s)
         (lambda (s)
           (if (pair? s)
             (cons (loop (car s))
                   (loop (cdr s)))
             (if (eq? s old) new s)))))
      (loop s))))

==>

(define subst-with-letrec-cps
  (lambda (old new s k)
    (letrec
      ((cps-loop (lambda (s k)
                   (if (pair? s)
         (cps-loop (car s)
                         (lambda (car-val)
                           (cps-loop (cdr s)
                                 (lambda (cdr-val)
                                   (k (cons
                                        car-val
                                        cdr-val))))))
                     (if (eq? s old)
                       (k new)
                       (k s))))))
      (cps-loop s k))))
```

```
(define subst-with-letrec
  (lambda (old new s)
    (letrec
      ((cps-loop (lambda (s k)
                   (if (pair? s)
                       (cps-loop (car s)
                                 (lambda (car-val)
                                   (cps-loop (cdr s)
                                             (lambda (cdr-val)
                                               (k (cons
                                                    car-val
                                                    cdr-val))))))
                       (if (eq? s old)
                         (k new)
                         (k s))))))
      (cps-loop s (lambda (x) x)))))
```

CPSing `if` and `let`

These follow our rules, too!

```
(k (if (foo x) ...  ...))  = (foo-cps x
                               (lambda (v)
                                 (k (if v ... ...))))
                           = (foo-cps x
                               (lambda (v)
                                 (if v (k ...) (k ...))))

(k (let ((y (foo x))) ...)) = (foo-cps x
                                (lambda (v)
                                  (k (let ((y v)) ...))))
                            = (foo-cps x
                                (lambda (v)
                                  (let ((y v)) (k ...))))
                            = (foo-cps x
                                (lambda (y)
                                  (k ...)))
```

Typed CPS Transformation

Let us consider CPS transformation of simply-typed λ-terms with call-by-value semantics.

$$\begin{array}{lrcl} \text{Types:} & t & ::= & t \to t \mid \mathsf{Int} \\ \text{Expressions:} & e & ::= & x \mid \lambda x.e \mid e_1 e_2 \end{array}$$

Here is a CPS transformation which is defined by a function $[\![\cdot]\!]$:

$$\begin{array}{rcl} [\![x]\!] & = & \lambda k.kx \\ [\![\lambda x.e]\!] & = & \lambda k.k(\lambda x.[\![e]\!]) \\ [\![e_1 e_2]\!] & = & \lambda k.[\![e_1]\!](\lambda v_1.[\![e_2]\!](\lambda v_2.(v_1 v_2)k)) \end{array}$$

Let o be a type of answers. Define t^* inductively:

$$\begin{array}{rcl} \mathsf{Int}^* & = & \mathsf{Int} \\ (s \to t)^* & = & s^* \to (t^* \to o) \to o \end{array}$$

Define $A^*(x) = t^*$ if $A(x) = t$.

Theorem If $A \vdash e : t$, then $A^* \vdash [\![e]\!] : (t^* \to o) \to o$.

The proof is by induction on the structure of the derivation of $A \vdash e : t$.

3 From Tail Form to First-Order Form

We've converted to tail form by using continuation-passing style. Now we want to get rid of all those higher-order functions.

```
(define remove-all-cps
  (lambda (a lsym k)
    (cond ((null? lsym)
           (k '()))
          ((eq? a (car lsym))
           (remove-all-cps a (cdr lsym) k))
          (else
            (remove-all-cps a (cdr lsym)
              (lambda (v) (k (cons (car lsym) v))))))))

(define remove-all
  (lambda (a lsym)
    (remove-all-cps a lsym (lambda (v) v))))
```

3.1 Continuations as a Datatype

Grammar for continuations

Continuation ::= `(lambda (v) v)`
::= `(lambda (v) (`*Continuation* `(cons (car lsym) v)))`

Interface Specification. (Remember $\lceil k \rceil$ means a representation of k).

`(make-identity)` $= \lceil$`(lambda (v) v)`$\rceil$
`(make-rem1 lsym` $\lceil k \rceil$`)` $= \lceil$`(lambda (v) (`k `(cons (car lsym) v)))`$\rceil$
`(apply-continuation` $\lceil k \rceil$ `v)` $=$ `(`k `v)`

3.2 Representation-Independent Code

```
(define remove-all-cps
  (lambda (a lsym k)
    (cond ((null? lsym)
   (apply-continuation k '()))
  ((eq? a (car lsym))
   (remove-all-cps a (cdr lsym) k))
  (else
    (remove-all-cps a (cdr lsym)
      (make-rem1 lsym k))))))

(define remove-all
  (lambda (a lsym)
    (remove-all-cps a lsym (make-identity))))
```

3.3 Procedural Representation of Continuations

```
(define make-identity
  (lambda ()
    (lambda (v) v)))

(define make-rem1
  (lambda (lsym k)
    (lambda (v)
      (apply-continuation k (cons (car lsym) v)))))

(define apply-continuation
  (lambda (k v)
    (k v)))
```

3.4 Abstract Syntax Tree Representation

Representation:

(make-identity) = '(identity-record)
(make-rem1 v k) = '(rem1-record v k)

Here the right-hand sides are patterns for list structures; the value of (make-rem1 v k) is a list whose first element is the symbol rem1, whose second element is the value of v, and whose third element is the value of k.

```
(define-record identity-record ())
(define-record rem1-record (lsym k))


(define apply-continuation
  (lambda (k v)
    (record-case k
      (identity-record () v)      ; this was (make-identity)
      (rem1-record (lsym k)       ; this was (make-rem1 lsym k)
        (apply-continuation k (cons (car lsym) v)))
      (else (report-bad-continuation k)))))

(define report-bad-continuation
  (lambda (k)
    (error 'apply-continuation
      "bad continuation ~s" k)))
```

3.5 Nifty Tree Representation

Since there's only one possible tag (`rem1`), we don't need to include it.

(`make-identity`) = `'()`
(`make-rem1` $lsym$ k) = ($lsym$. k)

```
(define make-identity
  (lambda ()
    '()))

(define make-rem1
  (lambda (lsym k)
    (cons lsym k)))

(define apply-continuation
  (lambda (k v)
    (if (null? k)
      v
      (let ((lsym (car k))
            (k1 (cdr k)))
        (apply-continuation k1
          (cons (car lsym) v))))))
```

3.6 Even Niftier Tree Representation

Like the previous, but store only `(car lsym)`, not `lsym`.

```
(make-identity) = '()
(make-rem1 lsym k) = `(,(car lsym) . ,k)
```

Here ` introduces a pattern; , marks a pattern expression, so `(,(car lsym) . ,k) denotes a cons-cell whose `car` is the value of the car of `lsym` and whose cdr is the value of `k`. This is `backquote` notation; see Dybvig.

```
(define make-identity (lambda () '()))

(define make-rem1
  (lambda (lsym k)
    (cons (car lsym) k)))

(define apply-continuation
  (lambda (k v)
    (if (null? k)
      v
      (let ((car-of-lsym (car k))
            (k1 (cdr k)))
        (apply-continuation k1
          (cons car-of-lsym v))))))
```

Another Case Study: `subst`

```
(define subst-cps
  (lambda (old new s k)
    (if (pair? s)
      (subst-cps old new (car s)
        (lambda (v1)
          (subst-cps old new (cdr s)
            (lambda (v2) (k (cons v1 v2))))))
      (if (eq? s old) (k new) (k s)))))

(define subst
  (lambda (old new s)
    (subst-cps old new s (lambda (x) x))))
```

Continuation ::= `(lambda (x) x)`

::= `(lambda (v1)`
`  (subst-cps old new (cdr s)`
`    (lambda (v2) (`*Continuation* `(cons v1 v2)))))`

::= `(lambda (v2) (`*Continuation* `(cons v1 v2)))`

Datatype of subst-Continuations

(make-identity) = $\lceil$(lambda (x) x)$\rceil$

(make-subst1 old new s $\lceil k \rceil$) = $\lceil$ (lambda (v1)
(subst-cps old new (cdr s)
(lambda (v2) (k (cons v1 v2))))))$\rceil$

(make-subst2 v1 $\lceil k \rceil$) = $\lceil$(lambda (v2) (k (cons v1 v2)))$\rceil$

(apply-continuation $\lceil k \rceil$ v) = (k v)

Representation-Independent Code

```
(define subst-cps
  (lambda (old new s k)            ; k is a representation
    (if (pair? s)
      (subst-cps old new (car s)
        (make-subst1 old new s k))
      (if (eq? s old)
        (apply-continuation k new)
        (apply-continuation k s)))))

(define subst
  (lambda (old new s)
    (subst-cps old new s (make-identity))))
```

Procedural Representation

```
(define make-identity
  (lambda ()
    (lambda (x) x)))

(define make-subst1
  (lambda (old new s k)
    (lambda (v1)
      (subst-cps old new (cdr s) (make-subst2 v1 k)))))

(define make-subst2
  (lambda (v1 k)
    (lambda (v2) (apply-continuation k (cons v1 v2)))))

(define apply-continuation
  (lambda (k v)
    (k v)))
```

Abstract Syntax Tree Representation

```
(define-record identity-record ())
(define-record subst1-record (old new s k))
(define-record subst2-record (v1 k))

(define apply-continuation
  (lambda (k x)
    (record-case k
      (identity-record () x)
      (subst1-record (old new s k)
        (let ((v1 x))
          (subst-cps old new (cdr s)
            (make-subst2 v1 k))))
      (subst2-record (v1 k)
        (let ((v2 x))
          (apply-continuation k (cons v1 v2))))
      (else (report-bad-continuation k)))))
```

3.7 List Representation of Continuations

List of Frames Representation

```
(make-identity) = '((lastframe))

(make-subst1 old new s k) = `((frame1 ,old ,new ,s) . ,k)

(make-subst2 v1 k) = `((frame2 ,v1) . ,k)
```

Typical continuation looks like a list of frames:

```
((frame1 <o> <n> <s_1>)
 (frame2 <v_1>)
 (frame2 <v_2>)
 ...
 (lastframe))
```

```
(define-record lastframe ())
(define-record frame1 (old new s))
(define-record frame2 (v1))

(define make-identity
  (lambda ()
    (cons (make-lastframe) '())))

(define make-subst1
  (lambda (old new s k)
    (cons (make-frame1 old new s) k)))

(define make-subst2
  (lambda (v1 k)
    (cons (make-frame2 v1) k)))

(define apply-continuation
  (lambda (k x)
    (let ((frame (car k))(k (cdr k)))
      (record-case frame
        (frame1 (old new s)
          (let ((v1 x))
            (subst-cps old new (cdr s) (make-subst2 v1 k))))
        (frame2 (v1)
          (let ((v2 x))
            (apply-continuation k (cons v1 v2))))
        (lastframe () x)
        (else (report-bad-continuation k))))))
```

List of Frames without Endmarker

Same as list-of-frames, except

```
(make-identity) = '()

(define make-identity
  (lambda () '()))

(define apply-continuation
  (lambda (k x)
    (if (null? k)  ; annoying to have to test this first!
      x
      (let ((frame (car k))(k (cdr k)))
        (record-case frame
          (frame1 (old new s)
            (let ((v1 x))
              (subst-cps old new (cdr s)
                (make-subst2 v1 k))))
          (frame2 (v1)
            (let ((v2 x))
              (apply-continuation k
                (cons v1 v2))))
          (else (report-bad-continuation k)))))))
```

Unframed List

Like list-of-frames, but without interior sublists

```
(make-identity) = '(lastframe)

(make-subst1 old new s k) = `(frame1 ,old ,new ,s . ,k)

(make-subst2 v1 k) = `(frame2 ,v1 . ,k)
```

Typical continuation looks like a list of items

```
(frame1 <o> <n> <s_1> frame2 <v_1> frame2 <v_2> ... lastframe)
```

```
(define make-identity
  (lambda ()
    '(lastframe)))

(define make-subst1
  (lambda (old new s k)
    (cons 'frame1 (cons old (cons new (cons s k))))))

(define make-subst2
  (lambda (v1 k)
    (cons 'frame2 (cons v1 k))))

(define apply-continuation
  (lambda (k x)
    (case (car k)
      ((frame1) (let ((old   (cadr k))
                      (new  (caddr k))
                      (s   (cadddr k))
                      (k   (cddddr k)))
                  (let ((v1 x))
                    (subst-cps old new (cdr s)
                      (make-subst2 v1 k)))))
      ((frame2) (let ((v1 (cadr k))
                      (k  (cddr k)))
                  (let ((v2 x))
                    (apply-continuation k (cons v1 v2)))))
      ((lastframe) x)
      (else (report-bad-continuation k))))))
```

3.8 Stack Representation of Continuations

Will start with unframed-stack representation, and represent the continuation as a real stack: an array and a pointer.

Will represent the stack as a Scheme vector (equivalent to an array: a randomly-accessible mutable data structure).

```
(define make-stack
  (lambda (size)
    (list '*stack -1 (make-vector size))))

(define stack->top cadr)
(define stack->data caddr)

(define stack-ref
  (lambda (stack ptr)
    (vector-ref (stack->data stack) ptr)))

;; works by side-effect
(define stack-set-val!
  (lambda (stack ptr val)
    (vector-set! (stack->data stack) ptr val)))

(define stack-set-top!
  (lambda (stack ptr)
    (set-car! (cdr stack) ptr)))
```

These work by side-effect, but return a pointer to the altered stack. This is convenient for composing stack operations (just like `cons`!)

```
(define stack-push
  (lambda (val stack)
    (let ((ptr (stack->top stack)))
      (stack-set-top! stack (+ ptr 1))
      (stack-set-val! stack (+ ptr 1) val)
      stack)))

(define stack-pop
  (lambda (stack n)
    (stack-set-top! stack (- (stack->top stack) n))
    stack))
```

Now that we are doing pointer arithmetic, some decent debugging tools are a must:

```
(define debug-print
  (lambda (stack)
    (if (eq? (car stack) '*stack)
      (begin
        (printf "sp = ~s~%" (stack->top stack))
        (let loop ((sp (stack->top stack)) (n 10))
          (if (or (< sp 0) (zero? n))
            (printf "~%")
            (begin
              (printf "stack[~s] = ~s~%" sp
                      (stack-ref stack sp))
              (loop (- sp 1) (- n 1))))))
      (printf "Warning: bad stack!~%stack = ~s~%" stack))))
```

Now we can alter the unframed-stack representation to use this array representation. Note that we are always using the *same* array, but we are modifying it destructively. This works just so long as we have only one continuation active at any time. If not, this will fail dramatically.

```
(define make-identity
  (lambda ()
    (let ((stack (make-stack 200)))    ; use some suitable size
      (stack-push 'lastframe stack))))

(define make-subst1
  (lambda (old new s k)
    (stack-push 'frame1        ; just change cons to stack-push
      (stack-push old
        (stack-push new
          (stack-push s k))))))

(define make-subst2
  (lambda (v1 k)
    (stack-push 'frame2
      (stack-push v1 k))))
```

```
(define apply-continuation
  (lambda (k x)                          ; k is a stack
    (debug-print k)
    (let ((sp (stack->top k)))
      (case (stack-ref k sp)
        ((frame1) (let ((old   (stack-ref k (- sp 1)))
                        (new   (stack-ref k (- sp 2)))
                        (s     (stack-ref k (- sp 3)))
                        (k     (stack-pop k 4)))
                    (let ((v1 x))
                      (subst-cps old new (cdr s)
                        (make-subst2 v1 k)))))
        ((frame2) (let ((v1 (stack-ref k (- sp 1)))
                        (k  (stack-pop k 2)))
                    (let ((v2 x))
                      (apply-continuation k
                        (cons v1 v2)))))
        ((lastframe) x)
        (else (report-bad-continuation k))))))
```

Testing

Here is a run, with a snapshot at every invocation of `apply-continuation`.

```
> (subst 'foo 'bar '((a foo) foo))
sp = 8
stack[8] = frame1
stack[7] = foo
stack[6] = bar
stack[5] = (a foo)
stack[4] = frame1
stack[3] = foo
stack[2] = bar
stack[1] = ((a foo) foo)
stack[0] = lastframe

sp = 10
stack[10] = frame1
stack[9] = foo
stack[8] = bar
stack[7] = (foo)
stack[6] = frame2
stack[5] = a
stack[4] = frame1
stack[3] = foo
stack[2] = bar
stack[1] = ((a foo) foo)
```

```
sp = 8
stack[8] = frame2
stack[7] = bar
stack[6] = frame2
stack[5] = a
stack[4] = frame1
stack[3] = foo
stack[2] = bar
stack[1] = ((a foo) foo)
stack[0] = lastframe

sp = 6
stack[6] = frame2
stack[5] = a
stack[4] = frame1
stack[3] = foo
stack[2] = bar
stack[1] = ((a foo) foo)
stack[0] = lastframe

sp = 4
stack[4] = frame1
stack[3] = foo
stack[2] = bar
stack[1] = ((a foo) foo)
stack[0] = lastframe
```

```
sp = 6
stack[6] = frame1
stack[5] = foo
stack[4] = bar
stack[3] = (foo)
stack[2] = frame2
stack[1] = (a bar)
stack[0] = lastframe

sp = 4
stack[4] = frame2
stack[3] = bar
stack[2] = frame2
stack[1] = (a bar)
stack[0] = lastframe

sp = 2
stack[2] = frame2
stack[1] = (a bar)
stack[0] = lastframe

sp = 0
stack[0] = lastframe

((a bar) bar)
```

3.9 Clever Representation of Continuations

Original:

```
(define fact
  (lambda (n)
    (if (zero? n) 1
      (* n (fact (- n 1))))))
```

CPS version:

```
(define fact-cps
  (lambda (n k)
    (if (zero? n)
      (k 1)
      (fact-cps (- n 1)
        (lambda (v) (k (* n v)))))))

(define fact
  (lambda (n)
    (fact-cps (lambda (v) v))))
```

Continuations for `fact`:

Continuation ::= `(lambda (v) v)`
::= `(lambda (v) (`*Continuation* `(* n v)))`

`(make-identity)` = $\lceil$`(lambda (v) v)`$\rceil$
`(make-fact1 n` $\lceil k \rceil$`)` = $\lceil$`(lambda (v) (`k `(* n v)))`$\rceil$

```
(define fact-cps
  (lambda (n k)
    (if (zero? n)
      (apply-cont k 1)
      (fact-cps (- n 1) (make-fact1 n k)))))

(define fact
  (lambda (n)
    (fact-cps n (make-identity))))
```

Claim: Every `fact` continuation is of the form

```
(lambda (v) (* p v))
```

for some `p`.

```
(lambda (v) v) = (lambda (v) (* 1 v))

If k = (lambda (v) (* p v))
then
(make-fact1 n k) = (lambda (v) (k (* n v)))
                 = (lambda (v) ((lambda (w) (* p w))
                                (* n v)))
                 = (lambda (v) (* p (* n v)))
                 = (lambda (v) (* (* p n) v))
```

So we can represent `(lambda (v) (* p v))` by just the number `p`. (Neat!)

```
(define make-identity
  (lambda () 1))

(define make-fact1
  (lambda (n p)      ; p       repr (lambda (v) (* p v))
    (* n p)))        ; (* n p) repr (lambda (v) (* (* n p) v))

(define apply-cont
  (lambda (p v)
    (* p v)))
```

```
(define fact-cps
  (lambda (n k)
    (if (zero? n)
      (apply-cont k 1)
      (fact-cps (- n 1) (make-fact1 n k)))))

(define fact
  (lambda (n)
    (fact-cps n (make-identity))))
```

Inlining these definitions in `fact-cps` we get:

```
(define fact-cps
  (lambda (n k)
    (if (zero? n)
        k     ; = (* k 1) = (apply-cont k 1)
        (fact-cps (- n 1) (* n k)))))

(define fact
  (lambda (n)
    (fact-cps n 1)
```

Wow! It's `fact-iter`! You won't be able to do things this dramatic too often, but you can make sense of many mysterious things as clever representations of continuations.

4 From First-Order Form to Imperative Form

Now we have tail-form, first-order (no first-class functions, just data structures) program. Want to convert it to flowchart. Will use idea of lambda-variables as registers: Replace

```
(define foo
  (lambda (x y) ..body..))
...
(foo E1 E2)
```

by

```
foo: ..body..   % take input from registers x and y


x := E1;        % be careful about overwriting registers here!
y := E2;
goto foo;
```

Will do this using Scheme instead of pseudocode.

```
;;; cps version, with representation-independent driver
;;; uses abstract syntax tree representation

(define-record identity ())
(define-record rem1 (lsym k))

(define remove-all
  (lambda (a lsym)
    (remove-all-cps a lsym (make-identity))))

(define remove-all-cps
  (lambda (a lsym k)
    (cond ((null? lsym)
           (apply-continuation k '()))
          ((eq? a (car lsym))
           (remove-all-cps a (cdr lsym) k))
          (else
            (remove-all-cps a (cdr lsym)
                  (make-rem1 lsym k))))))

(define apply-continuation
  (lambda (k v)
    (record-case k
      (identity () v)
      (rem1 (lsym k1)
        (apply-continuation k1 (cons (car lsym) v))))))
```

```
;;; register machine version

(define remove-all
  (lambda (a lsym)
    (let ((a a) (lsym lsym)
          (k (make-identity))
          (v '*unbound*))
      (letrec
        ((remove-all-cps
           (lambda ()
             (cond ((null? lsym)
                    (set! v '())
                    (apply-continuation))
                   ((eq? a (car lsym))
                     (set! lsym (cdr lsym))
                     (remove-all-cps))
                   (else
                     (set! k (make-rem1 lsym k))
                     (set! lsym (cdr lsym))
                     (remove-all-cps)))))
         (apply-continuation
           (lambda ()
             (record-case k
               (identity () v)
               (rem1 (lsym k1)
                     (set! k k1)
                     (set! v (cons (car lsym) v))
                     (apply-continuation))))))
        (remove-all-cps)))))
```

Now let's do it for `subst`. Let's take the array representation:

```
(define subst
  (lambda (old new s)
    (subst-cps old new s (make-identity))))

(define subst-cps
  (lambda (old new s k)       ; k is a representation
    (if (pair? s)
      (subst-cps old new (car s)
        (make-subst1 old new s k))
      (if (eq? s old)
        (apply-continuation k new)
        (apply-continuation k s)))))

(define make-identity
  (lambda ()
    (let ((stack (make-stack 200)))  ; use some suitable size
      (stack-push 'lastframe stack))))

(define make-subst1
  (lambda (old new s k)
    (stack-push 'frame1       ; just change cons to stack-push
      (stack-push old
        (stack-push new
          (stack-push s k))))))

(define make-subst2
  (lambda (v1 k)
    (stack-push 'frame2 (stack-push v1 k))))
```

```
(define apply-continuation
  (lambda (k x)                          ; k is a stack
    (let ((sp (stack->top k))
          (ins (stack-ref k sp)))
      (case ins
        ((frame1) (let ((old   (stack-ref k (- sp 1)))
                        (new   (stack-ref k (- sp 2)))
                        (s     (stack-ref k (- sp 3)))
                        (k     (stack-pop! k 4)))
                    (let ((v1 x))
                      (subst-cps old new (cdr s)
                        (make-subst2 v1 k)))))
        ((frame2) (let ((v1 (stack-ref k (- sp 1)))
                        (k  (stack-pop! k 2)))
                    (let ((v2 x))
                      (apply-continuation k
                        (cons v1 v2)))))
        ((lastframe) x)
        (else (report-bad-continuation k))))))
```

```
(define subst
  (lambda (old-arg new-arg s-arg)
    ;; (subst-cps old new (make-identity))
    (set! old old-arg)
    (set! new new-arg)
    (set! k (make-identity))
    (subst-cps)))

(define subst-cps
  (lambda ()                  ; uses old, new, s, k
    (if (pair? s)
      ;; (subst-cps old new (car s)
      ;;   (make-subst1 old new s k))
      (begin
        (set! k (make-subst1 old new s k))
        (set! s (car s))
        (subst-cps))
      (if (eq? s old)
        (begin
          ;; (apply-continuation k new)
          (set! x new)
          (apply-continuation))
        (begin
          ;; (apply-continuation k s)
          (set! x s)
          (apply-continuation))))))
```

```
(define apply-continuation
  (lambda ()                              ; uses k, x
    (let ((sp (stack->top k))
          (ins (stack-ref k sp)))
      (case ins
        ((frame1) (let
                    ;; need different local names
                    ((old1   (stack-ref k (- sp 1)))
                     (new1   (stack-ref k (- sp 2)))
                     (s1     (stack-ref k (- sp 3)))
                     (k1     (stack-pop! k 4)))
                    (let ((v1 x))
                      ;;(subst-cps old new (cdr s)
                      ;; (make-subst2 v1 k))
                      (set! old old1)
                      (set! new new1)
                      (set! s (cdr s1))
                      (set! k (make-subst2 v1 k1))
                      (subst-cps))
        ((frame2) (let
                    ((v1 (stack-ref k (- sp 1)))
                     (k1  (stack-pop! k 2)))
                    (let ((v2 x))
                      ;; (apply-continuation k
                      ;;  (cons v1 v2))
                      (set! x (cons v1 v2))
                      (set! k k1)
                      (apply-continuation)))
        ((lastframe) x)
        (else (report-bad-continuation k))))))
```